



### Specification

- TYP A** - version with 4 holes
- TYP B** - version with 4 threaded pins
- TYP C1** - version with 2 holes and 2 threaded pins
- TYP C2** - version with 2 threaded pins and 2 holes
- TYP D** - version with 5 holes

### INFORMATION

- Type A, C1, C2, D: use **DIN 965** screws
- Pin made of **AISI 304** stainless steel
- M6 screws made of **AISI 304** stainless steel
- M8 screws made of galvanized steel

### Material: ZAMAK 5

CATALOG NO.	TYPE	L1	L2	c	h1	h2	b1	b2	b3	b4	t1	t2	d1	d2	d3	FINISH
3.509.01	A	63	50	-	-	-	28	15	30	-	11	6	6	6,5	11,5	Chrome
3.509.02	A	63	50	-	-	-	28	15	30	-	11	6	6	6,5	11,5	RAL9005
3.509.31	B	63	50	M6	11,5	-	28	15	30	-	11	6	6	6,5	11,5	Chrome
3.509.32	B	63	50	M6	11,5	-	28	15	30	-	11	6	6	6,5	11,5	RAL9005
3.509.11	D	63	50	-	-	-	28	15	30	15	11	6	6	6,5	11,5	Chrome
3.509.12	D	63	50	-	-	-	28	15	30	15	11	6	6	6,5	11,5	RAL9005
3.512.11	A	90	60	-	-	-	45	18	36	-	15	8	8	8,4	15,5	Chrome
3.512.12	A	90	60	-	-	-	45	18	36	-	15	8	8	8,4	15,5	RAL9005
3.512.21	B	90	60	M8	15,4	15	45	18	36	-	15	8	8	-	-	Chrome
3.512.22	B	90	60	M8	15,4	15	45	18	36	-	15	8	8	-	-	RAL9005
3.512.31	C1	90	60	M8	-	15	45	18	36	-	15	8	8	8,4	15,5	Chrome
3.512.32	C1	90	60	M8	-	15	45	18	36	-	15	8	8	8,4	15,5	RAL9005
3.512.41	C2	90	60	M8	15,4	-	45	18	36	-	15	8	8	8,4	15,5	Chrome
3.512.42	C2	90	60	M8	15,4	-	45	18	36	-	15	8	8	8,4	15,5	RAL9005

### Material: STAINLESS STEEL AISI 316

CATALOG NO.	TYPE	L1	L2	c	h1	b1	b2	b3	b4	t1	t2	d1	d2	d3	FINISH
3.509.0SN	A	63	50	-	-	28	15	30	-	11	6	6	6,5	13,5	-
3.509.3SN	B	63	50	M6	12	28	15	30	-	11	6	6	-	-	-
3.512.1SN	A	90	60	-	-	45	18	36	-	15	8	8	8,4	18,3	-
3.512.2SN	B	90	60	M8	14	48	18	36	-	15	8	8	-	-	-